



iIMAGE LIFT

The Moving Image Lift mounts to the rear wall of an auditorium. It consists of a quiet projector enclosure 'pod' riding on a vertical track. The system raises the projector into position where it will have a clear sightline to the screen for projection, and lowers it to a convenient height for service. The product facilitates a "boothless" cinema design.



Features:

- Automatic safety interlock
- Key switch to raise and lower the unit included
- Various projection heights may be selected at installation.
- All parts made from rugged formed and welded steel
- Projector enclosure has removable side panels for service
- 24" sq. projection port included as standard with water-clear, A/R coated glass
- Interface plate at the top of the system facilitates electrical and HVAC connections
- Includes 8RU of standard 19" rack mounting under the projector.



Site Requirements:

The system requires a load-bearing wall at the rear of the auditorium. Alternatively the wall must be reinforced with additional steel or heavy gage studs (details available on request).

Power Requirements:

The system requires a dedicated 120VAC, 15A circuit for the hoist (in addition to the power required for the projector).

Part Number: A000410-001 Lift System, 12'-0" track height, 141" max. enclosure ht.
A000410-002 Lift System, 13'-6" track height, 159" max. enclosure ht.

** Due to ongoing development, features and specifications subject to change without notice.*



MOVING IMAGE TECHNOLOGIES
YOUR DIGITAL CINEMA EXPERTS